

# Ultrasonic Lab500 for Cup Horn Low Power

## TYPICAL APPLICATIONS



- Enzyme/DNA extraction
- Reaction acceleration
- Bacterial destruction
- Sonochemistry
- Cell lysis
- Extraction...

## FEATURES

### CUP HORN

#### Cup Horn 22kHz

- Output power: 50W<sub>eff</sub>
- Dimensions (DxL) : 119x125mm

#### Cup Horn 28kHz

- Output power : 50W<sub>eff</sub>
- Dimensions (DxL) : 119x125mm

#### Cup Horn 40kHz

- Output power : 50W<sub>eff</sub>
- Dimensions (DxL) : 119x90mm

#### Cup Horn 80kHz

- Output power : 50W<sub>eff</sub>
- Dimensions (DxL) : 119x125mm

#### Cup Horn 100kHz

- Output power : 50W<sub>eff</sub>
- Dimensions (DxL) : 119x90mm



#### NexTgen Lab500 generator

- Max. power : 500W<sub>RMS</sub>
- Amplitude setting : 10% - 100%
- Operating frequency : regulation on optimal frequency
- Dimensions (LxWxH) : 390x145x148mm
- US Start/stop by Labtablet, dry contact, footswitch, or PC

#### Cup Horn

- Air cooling input/output
- Material: Stainless Steel

#### Reactor

- Temperature setting available
- Max. volume treatment: 285mL
- Material : Stainless steel

#### Maximum conditions

- Temperature: 70°C
- Pression: 2 bars relative pressure

LabTablet for intuitive setting  
« Start » NexTgen Software version

# OPTIONS

## LabPremium software - traceability, temperature-related operation, worldwide remote assistance

In addition to the functions of our « Start » software, full traceability of the processes is guaranteed by continuous registration of all data and the possibility of its exportation to Excel (data logger principle).

Our **LabPremium** software likewise enables to link the operation of the equipment to temperature conditions. For example, as soon as a certain sample temperature is reached, the operation stops or continues by cycles, according to your settings.


The **LabPremium** is also particularly appreciated for its “quick diagnosis” functionality and the given possibility of worldwide remote assistance.



# ACCESSORIES

<b>SOUND DAMPING ENCLOSURE</b>	Dimensions (HxWxL) : approx. 800x400x400mm.
<b>TEMPERATURE SENSOR</b>	Associated with the NextGen LabPremium software, it enables to control and master the sample temperature during operation.
<b>EPPENDORF SUPPORT</b>	On request. This accessory requires a non-standard reactor.
<b>OPERATING MODE ON REQUEST</b>	Continuous, Non-oxidizing atmosphere, Under pressure

Your local distributor



SinapTec

Synergie park, 7 Avenue Pierre et Marie Curie FR-59260 Lezennes

+33 (0)3 20 61 03 89

sinaptec@sinaptec-ultrasonic.com